

## DREAMSCAPE PHYSICAL PROPERTIES & SPECIFICATIONS

### PRODUCT PACKAGING

Each roll is meticulously packaged in a re-usable suspension box or ultra sturdy tube.

**(No flat spots, no creases, no splices.)**

*STD Lengths: 75', 150', 300'*

*STD Widths: 30", 48", 54", 60", 75"*

*(+/-1/8")*

*Core Diameter: 3 inches i.d. Heavy-Duty*

*\*Custom Lengths and widths available upon request.*

### PHYSICAL PROPERTIES

*Product Weight: 200oz. Per lineal yd., (13oz. Per sq. yd.)*

*Vinyl Weight: 17oz. Per lineal yd.*

*Fabric Weight: 3oz. Per lineal yd.*

*Thickness: 0.015 to 0.030 in.*

*\*depending on texture*

*Fabric: Poly-Cotton Osnaburg or Polyester Nonwoven*

*\*depending on texture*

### BREAKING STRENGTHS, LBS. FORCE

*Machine Direction-warp:*

*\*Exceeds Type II minimum of 50lbs.*

*Cross Machine Direction-fill:*

*\*Exceeds Type II minimum of 55lbs.*

### TEARING STRENGTH, SCALE

*Machine Direction-warp:*

*\*Exceeds Type II minimum of 25lbs.*

*Cross Machine Direction-fill:*

*\*Exceeds Type II minimum of 25lbs*

### COLD CRACK RESISTANCE AT 20° F

No change

### HEAT AGING (7 DAYS AT 158° F)

\*Does not become stiff, brittle, discolored, or show loss of grain

### SPECIFICATIONS/ TESTING/ CERTIFICATION

*Federal Specification:*

*\*CCC-408-D,C,B,A \*Type II \*Class A*

*CFFA Specification:*

*\*CFFA-W-101-D \*Type II \*Class A*

### FIRE TESTING

*ASTM-E84 Tunnel Test Class A*

*NFPA286 Corner Burn Test Class A*

*NFPA265 Corner Burn Test Class A*

*BS476 Part 6&7*

*\*Meets or exceeds requirements for flame spread, smoke developments, and flashover.*

### MOLD/ MILDEW/ BACTERIAL RESISTANCE

*ASTM-G21 Specifications: Passed all requirements of CCCW-408-D*

### ENVIRONMENT

*NYC MEA: Register*

*\*Cadmium and Lead Free Formulation*

