

Contempo SAV

Contempo SAV is an economical, universal and permanent self adhesive vinyl film (PVC) with a water resistant, matte top inkjet coating.



Uses:

Applications include indoor floor graphics, indoor signage, short term outdoor signage, window graphics.

Advantages:

Flexible PVC base (vinyl), matte waterfast coating, permanent water-based glue, excellent hot and cold lamination, good color brilliance, robust and flexible base for uneven surfaces.

Catalog #	Size
2136	36" x 100'
2142	42" x 100'
2150	50" x 100'
2160	60" x 100'

Specifications:

Caliber	3.5 mil PVC Film
Adhesive	Permanent Acrylic
Ink	Dye or UV/Pigment
Waterfast / Waterproof	Waterfast with dye. Waterproof with UV pigment ink.
Outdoor Durability	3 month un laminated when printd with UV inks. One year with UV inks and pressure sensitive laminate.
Application Temperature	55° to 85°F
Finishing	Use any pressure sensite laminate. Can be used with hot laminates for short term indoor use.

Application	Laminate
Long Term Floor Graphics	InstaShield FG
Short Term Floor Graphics	Ri-Jet Floortalker Economy
Short Term Indoor Signage	InstaShield Lustre E HardGuard Laminates
Dry Erase Boards	InstaShield Dry Erase Laminate
Outdoor Signage	InstaShield Lustre E

Printing Tips: Always use gloves when handling rolls. Always print on the outside of roll. To insure best print performance of this media, clean and calibrate cartridges before loading the paper. While loading the HP 5000/5500/6100 printer, only feed 6" of paper beyond print heads. This will prevent alignment errors and banding. For best results, print in 60° to 85° and 40% to 60% RH.

Storage: New rolls - 50° to 86°F. 20 to 70% RH. Open Rolls - cover rolls with plastic bag, use end cap if storing on end. Do not stack rolls. Allow material time to adapt to room conditions.

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality will not be held responsible for customers end use of product. Quality is available for directions and advice as to proper use and application of our products.

800/552-9427

www.qmls.com