

DuraPrint Perforated



DuraPrint Perforated Film is a unique rigid vinyl film with a bright white front side and reverse black side and 1.5mm perforations for one-way viewing. It features 30% open area and 70% print area for maximum contrast and print definition.

Uses:

Posters, room dividers or advertising on windows.

Advantages:

This perforated film can be applied in many different and cost effective ways - on advertisement space which has not been used up to now.

Catalog #	Size
DuraPrint Perforated	
14954100	54" x 100'
InstaTack Tape	
2490482	4.95"x82' (2 per box)
2490882	8.9"x82'
2491782	17.7"x82'
2493582	35.5"x82'



Specifications:

Thickness: 200 microns/.2 mil

Film: Vinyl

Ink: Solvent,eco-solvent and UV curable.

Tear Resistance: Excellent

Flammability: Not Tested

Humidity Resistance: Yes

Durability: One year Indoor Application

Shelf Life: 1 year at 41°F-104°F, RH 20%-70%

Service Temperature Range: 41°F-104°F, RH 30%-70%

Finishing: Use *InstaTack Tape micro dot transfer adhesive tape to apply to the inside of windows.

*If applied in combination with InstaTack Tape, formation of wrinkles might be probable under certain circumstances. Quality cannot take responsibility for this occurrence

INSTALLATION GUIDE

Manual Application

Lay print face up on table surface. (Be sure ink on print is completely dry.)

Apply InstaTack Tape to the surface of the print. Ensure that all edges and at least 50% of the surface are covered. To ensure perfect lay-flat on the window and better overall adhesion, 100% coverage is recommended.

Gently burnish to print side with sign maker's plastic squeegee or with palm of your hand.

Leave release liner on InstaTack Tape until ready to install.

Application With Use of Laminator

Make sure laminator is cold!

Apply InstaTack Tape to the printed surface by using lightest pressure settings on the rolls.

Rolls of InstaTack Tape can be run side-by-side on laminators. Small sections of blank cores can be used to spread the rolls, to ensure that the edges of the print are covered.

Leave release liner on InstaTack Tape until ready to install.

**For best adhesion and easiest clean-up, apply InstaTack Tape to print at least 12 hours prior to installation.*

1. Cut poster to desired size.
2. Roll it into tube with InstaTack Tape adhesive liner on outside.
3. At job site, remove InstaTack Tape adhesive liner.
4. Use squeegee to dry apply print to glass.

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality will not be held responsible for customers end use of product. Quality is available for directions and advice as to proper use and application of our products.

6/11/2009

800/552-9427

www.qmls.com