

DuraVinyl

DuraVinyl is available as a cast or calendared vinyl film specially formulated for solvent ink jet printing. It is offered as a 2, 3,2,3.5 or 6 mil vinyl in a wide range of adhesive/film combinations.



DuraVinyl Calendared Vinyl

A 3 to 5 year outdoor durable calendared vinyl in Gloss White, Matte White or Gloss Clear. Available with permanent, removable or low-tack adhesives and a 90 lb. poly-coated release liner.

Catalog #	Size
DuraVinyl 201 Gloss White, Moderate Tack Perm Adh	
Applications: POP, Indoor and Outdoor Signage	
0920130	30"x150'
0920154	54"x150'
0920160	60"x150'
DuraVinyl 202 Gloss White, Ultra Low-tack Adhesive	
Applications: Indoor Wall graphics, POP, Indoor Signage, Window, Floor	
0920230	30"x150'
0920254	54"x150'
0920260	60"x150'
DuraVinyl 205 Gloss White, Hi-Tack Perm Adh	
Applications: Outdoor Signage, Can be "wet applied".	
0920530	30"x150'
0920554	54"x150'
0920560	60"x150'
DuraVinyl 251 Matte White, Permanent Adhesive	
Applications: Indoor or Outdoor Signage, POP	
0925130	30"x150'
0925154	54"x150'
0925160	60"x150'
DuraVinyl 252 Matte White, Ultra Low-Tack Adhesive	
Applications: Indoor Wall Graphics, POP Indoor Signage, Window, Floor	
0925230	30"x150'
0925254	54"x150'
0925260	60"x150'
DuraVinyl 253 Matte White, Removable Adhesive	
Applications: Outdoor Window Graphics, Floor, Carpet	
0925330	30"x150'
0925354	54"x150'
0925360	60"x150'
DuraVinyl 254 Matte White, Gray Blockout Adhesive	
Applications: Long Term Signage, POP, Floor, Carpet. Can be "wet applied".	
0925454	54"x150'

Catalog #	Size
DuraVinyl 261 Gloss Clear, Permanent Adhesive	
Applications: Outdoor Signage	
0926130	30"x150'
0926154	54"x150'
0926160	60"x150'
DuraVinyl 262 Gloss Clear, Ultra Low-Tack Adhesive	
Applications: Interior Window Graphics, Use with Window Cal II	
0926230	30"x150'
0926254	54"x150'
0926260	60"x150'
DuraVinyl 263 Gloss Clear, Low-Tack Adhesive	
Applications: Interior Window Graphics, Use with WindowCal II	
0926330	30"x150'
0926354	54"x150'
0926360	60"x150'
DuraVinyl 272 Translucent White, Moderate Tack Rem Adhesive	
Applications: Indoor and Outdoor Backlits	
0927254	54"x150'
0927260	60"x150'
DuraVinyl 352 Matte, White, Ultra Low Tack Adhesive	
Applications: Short Term Interior Wall Graphics, Wall Decals	
0935260	60"x150'
0935260-750	60"x750'
DuraVinyl 355 Matte, White, Permanent Adhesive	
Applications: POP, Trade Show, Window	
0935554	54"x150'
0935560	60"x150'
0935560-750	60"x750'

DuraVinyl Premium Cast Vinyl

A 7 year outdoor durable cast vinyl specifically formulated for solvent ink jet printing. Available in Gloss White, Semi-Gloss White, and Gloss Clear. Vehicle, fleet and extended durability applications.

Catalog #	Size
DuraVinyl 501 Gloss White, Permanent	
0950148	48"x150'
0950154	54"x150'
0950160	60"x150'
DuraVinyl 502 High Gloss White, Gray Blockout	
0950248	48"x150'
0950254	54"x150'
0950260	60"x150'
DuraVinyl 503 Semi-Gloss White, Gray Blockout	
09250348	48"x150'
09250354	54"x150'
09250360	60"x150'

Catalog #	Size
DuraVinyl 504 Clear Gloss, Permanent	
0950448	48"x150'
0950454	54"x150'
0950460	60"x150'
DuraVinyl 505 Gloss White, Repositionable Gray Blockout	
0950548	48"x150'
0950554	54"x150'
0950560	60"x150'
DuraVinyl 702 Gloss White, Gray Back, Repositionable Adh, Air Flow Release Liner	
0970254	54"x150'
0970260	60"x150'
0970260-750	60"x750'

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality will not be held responsible for customers end use of product. Quality is available for directions and advice as to proper use and application of our products.

DuraVinyl Specifications

Calendared Vinyl					
	DuraVinyl 201	DuraVinyl 202	DuraVinyl 205	DuraVinyl 251	DuraVinyl 252
Face Material	3.5 mil flexible vinyl	3.5 mil flexible vinyl	3.5 mil flexible vinyl	3.4 mil flexible vinyl	3.4 mil flexible vinyl
Color/Finish	Gloss White	Gloss White	Gloss White	Matte White	Matte White
Adhesive	Permanent Acrylic	Removable acrylic	High tack permanent acrylic	Permanent acrylic	Removable ultra low-tack acrylic
Liner	90# polycoated bleached layflat	90# polycoated bleached layflat	90# polycoated bleached layflat	90# polycoated bleached layflat	90# polycoated bleached layflat
Min. Appl. Temp	50°F	50°F	50°F	50°F	50°F
Service Temp	-40°F to +180°F	-40°F to +180°F	-40°F to +180°F	-40°F to +180°F	-40°F to +180°F
Outdoor Durability	3 years	3 years/6 month avg removability	3 years	3 years	3 years/6 month avg removability
Shelf Life	2 years	2 years	2 years	2 years	2 years

Calendared Vinyl					
	DuraVinyl 253	DuraVinyl 254	DuraVinyl 261	DuraVinyl 262	DuraVinyl 263
Face Material	3.4 mil flexible vinyl	3.5 mil flexible vinyl	3.5 mil flexible vinyl	3.5 mil flexible vinyl	3.5 mil flexible vinyl
Color/Finish	Matte White	Matte White	Gloss Clear	Gloss Clear	Gloss Clear
Adhesive	Medium-tack, removable acrylic	Hi-tack perm, acrylic, gray	Permanent acrylic	Removable ultra low-tack acrylic	Removable low tack acrylic
Liner	90# polycoated bleached layflat	90# polycoated bleached layflat	90# polycoated bleached layflat	90# polycoated bleached layflat	72# high-release Kraft
Min. Appl. Temp	50°F	50°F	50°F	50°F	50°F
Service Temp	-40°F to +180°F	-40°F to +180°F	-40°F to +180°F	-40°F to +180°F	-40°F to +180°F
Outdoor Durability	3 years/6 month avg removability	3 years	3 years	3 years/6 month avg removability	3 years/6 month avg removability
Shelf Life	2 years	2 years	2 years	2 years	3 years

Calendared Vinyl					
	DuraVinyl 272	DuraVinyl 352	DuraVinyl 355		
Face Material	3.2 mil flexible translucent vinyl	6.0 mil semi-rigid vinyl	6.0 mil semi-rigid vinyl		
Color/Finish	Translucent White Semi Gloss	Matte White	Matte White		
Adhesive	Medium-tack, removable acrylic	Low peel removable acrylic	Permanent acrylic		
Liner	90# polycoated bleached layflat	90# polycoated bleached layflat	90# polycoated bleached layflat		
Min. Appl. Temp	50°F	50°F	50°F		
Service Temp	-40°F to +180°F	-40°F to +180°F	-40°F to +180°F		
Outdoor Durability	3 years	5 years	3 years		
Shelf Life	2 years	2 years	2 years		

Premium Cast Vinyl			
	DuraVinyl 501	DuraVinyl 502	DuraVinyl 503
Face Material	2.0 mil flexible cast vinyl	2.0 mil vinyl, gray blockout primer	2.0 mil vinyl, gray blockout primer
Color/Finish	Gloss white	High gloss white	Semi-gloss white
Adhesive	Permanent acrylic	Permanent acrylic	Permanent acrylic
Liner	90# polycoated bleached layflat	90# polyethylene 2-side layflat	90# polyethylene 2-side layflat
Min. Appl. Temp	50°F	45°F	45°F
Service Temp	-40°F to +180°F	-50°F to +225°F	-50°F to +225°F
Outdoor Durability	7 to 9 years	7 years	7 years
Shelf Life	2 years	2 years	2 years

Premium Cast Vinyl			
	DuraVinyl 504	DuraVinyl 505	DuraVinyl 702
Face Material	2.0 mil clear cast vinyl	2.0 mil vinyl, gray blockout primer	2.0 mil vinyl, gray blockout primer
Color/Finish	Gloss Clear	Gloss White	Gloss White
Adhesive	Permanent acrylic	Permanent acrylic Repositionable at application	Semi-permanent acrylic Repositionable at application
Liner	90# polycoated 2-side layflat	90# polycoated 2-side layflat	90# polycoated 2-sides, air release liner
Min. Appl. Temp	40°F	40°F	55°F
Service Temp	-50°F to +225°F	-50°F to +225°F	-50°F to +225°F
Outdoor Durability	7 years	7 years	7 years
Shelf Life	2 years	2 years	2 years