

HardGuard Diamond



Hard Guard Diamond is a 6 mil thermal laminate that features a low melt adhesive system with UV inhibitors and a fine textured surface that is specially designed for pop-up display panels and other trade show graphics.

Uses:

For tradeshow graphics and pop-up displays, Hard Guard Diamond is the answer. It allows brilliant colors to shine through and has the ability to withstand the rugged environments required for tradeshow graphics and pop-up displays.

Advantages:

Scratch resistant, non-reflective surface for graphic enhancement.

Laminate Hard Diamond over paper with either HardGuard White or HardGuard Light Stop for a durable, rollable tradeshow panel.

Catalog #	Size
0680715	25"x250'
0680725	38"x250'
0680750	51"x250'
0680760	55"x250'
0680770	61"x250'
0680790	76"x250'

Specifications:

Film	1 mil embossed OPP(Oriented Polypropylene) sandwiched to a 2 mil polyester.
Adhesive	3 mil Polyethylene
UVA Absorption	85% minimum (Test method Perkin-Elmer Spectrometer)
UVB Absorption	100% minimum (Test method Perkin-Elmer Spectrometer)
Finishing	Use with Hard White 5 or 10 mil, HardGuard Light Stopper 5, 10 or 15 mil, or any of our other Hard Guard or DigiGuard products.
Service Temperature Range	180°F to 230°F Indoor (This is not a laminator setting.)
Application Temperature	190°F to 205°F
Storage Conditions	50-85°F, 40-80% RH. Store in original packaging.
Shelf Life	One year from ship date when stored in proper conditions.

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality will not be held responsible for customers end use of product. Quality is available for directions and advice as to proper use and application of our products.

8/27/2008

800/552-9427

www.qmls.com