



## Smart Banner

Smart Banner is a light and flexible vinyl banner with a smooth print surface. It is designed for indoor and outdoor use and is waterfast with pigmented inks. Smart Banner consists of polyester scrim sandwiched between two vinyl layers which provides good tear resistance.

**Uses** Free hanging indoor/outdoor banners. Can be hung by grommets on the corners or by “pocketing” the top and bottom by sewing or use of double sided tape. The coating is designed for high ink limit, excellent white point, and good scratch resistance without lamination. Waterfast with pigmented inks. Won’t crack, fade or peel outdoors, without lamination (minimum) three months. Lamination with Instashield UV Lustre or Instashield UV Matte is recommended for outdoor use of longer than 3 months or in applications susceptible to dirt or abrasion. On printers equipped with “on board” cutter, cutter mechanism should be disabled due to the high tensile strength of the scrim vinyl substrate.

Size	Catalog #
36" x 40'	4336
42" x 40'	4342
50" x 75'	4350
60" x 40'	4360

Specifications	
Weight	105lb
Thickness	15 mil
Converting	Coated side out.
Lamination	Can be overlaminated with Instashield UV Lustre or Instashield UV Matte laminates to increase UV stability and scratch resistance. Laminate with cold rollers to prevent curl.
Whiteness	98W (CIE)
Storage	New rolls = 50° to 86°F. 35-65% relative humidity Open rolls = Cover roll with plastic bag, use end cap if storing on end, do not stack rolls

PRINTER COMPATIBILITY	
Printer	Ink
HP 2000/2500/2800/3000/3500/5000/5500	Dye or UV
Encad Pro 600e/630/700/750/850	Dye or UV
Epson 3000/7000/7500/7600 / 9000/9600/10600	Dye or UV
Roland Hi-Fi Jet	Dye or UV
Mimaki JV-2	Dye or UV
Mutoh RJ 4100/6100	Dye or UV



Quality Media & Laminating Solutions, Inc.  
285 State Street, Suite One  
North Haven, CT 06473  
1-800-552-9427 FAX 203 281-6451  
info@qmls.com www.qmls.com

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality will not be held responsible for customers end use of product. Quality is available for directions and advice as to proper use and application of our products.