



2-Way Window Film

2-Way Window Film is a reverse print, translucent, 6 mil polyester film with a low tack adhesive and release liner on the backside. When mounted on windows, image is viewable from either side in reflected or transmitted light.

Uses

2-Way Window Film is used for reverse print backlit on windows and lightboxes. Print and trim to size for intended window - peel back 2-3 inches of release liner along the top of the print and affix the top of the image to the window or mounting surface. Continue to peel back the release liner while smoothing the film onto the window. The inherent stiffness of the polyester film, together with the special adhesive, allows a smooth, bubble-free installation. Removable without adhesive residue. Especially effective at night when inside lights turn storefront windows into a lightbox!

Size	Catalog #
36" x 60'	8336
50" x 60'	8350

Printer	Dye Inks	UV Inks
Mutoh RJ 4100/6100		X
Encad Pro 600e/630/700/750/850	X	X
HP 2000/2500/2800/3000--3500/5000/5500/1050	X	X
Roland HiFiJet	X	X
Mimaki JV-2/JV 1300		X
Epson 7000/7500/9000/9500	X	

Specifications	
Total weight	160g/m ² (42 lb)
Thickness	6 mil
Transparency	1.5 (UV-filter) Optical density
Converting	Material is converted coated side out
Printer/Ink Compatibility	Can be printed with waterbased dye inks and pigmented inks. Using light-stable inks will increase image longevity.
Printer Settings	Ink limit = 380% (Individual results may vary due to printer type, shop conditions, and image.) Media type = Coated paper Print mode = Best Resolution = up to 1440 dpi (Individual resolution settings may vary due to printer type)
Lamination	Can be overlaminated with Instashield Gloss, Lustre or Matte laminates to enhance durability.
Outdoor Durability	Indoor use only.
Service Temperature Range	55°F - 85°F
Minimum Application Temperature	55°F
Shelf Life	12 months
Storage	New rolls = 50° to 86°F. 35-65% relative humidity Open rolls = Cover roll with plastic bag, use end cap if storing on end, do not stack rolls

Ordering

2-Way Window Film is stocked in all QMLS distribution centers and available for immediate delivery. [Click here](#) to order online, or call 1-800-552-9427.



Quality Media & Laminating Solutions, Inc.
285 State Street, Suite One
North Haven, CT 06473
1-800-552-9427 FAX 203 281-6451
info@qmls.com www.qmls.com

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality will not be held responsible for customers end use of product. Quality is available for directions and advice as to proper use and application of our products.