



IJ Polycarbonate Clear

IJ Polycarbonate Clear is a printable polycarbonate with a velvet-textured surface and a clear coating.

Uses

Tradeshow graphics, floor graphics, and backlit graphics all benefit from IJ Polycarbonate Clear. Its unique coating technology allows more ink to pass through the backlit coating for outstanding true-color results. When combined with any of our Pressure Sensitive Backers, IJ Polycarbonate Clear offers superb protection against tunneling and delamination.

The QMLS difference

In today's fast-changing marketplace, we know how important it is to have a reliable source. Not just of products, but of knowledge and information. When you choose QMLS, you get someone who's as committed to the quality of your end product as you are. Someone who knows the options inside and out, and can help you choose the one that's best suited to your needs.

	Size	Catalog #
HP Printers	36" x 60'	6836
	50" x 50'	6850
All Other Printers	36" x 60'	6136
	50" x 50'	6150

Specifications	
<i>Caliper</i>	10 mil (254 micron)
<i>Optimal Service Environment</i>	Printing = 73°F, 50% relative humidity End use = -40° to +176°F
<i>Printer Compatibility</i>	Compatible with most thermal and piezo ink jet printers, including Encad, ColorSpan, HP, and Epson.
<i>Ink Compatibility</i>	Compatible with most aqueous dye inks printed with a thermal or piezo ink jet printer. Use of pigment inks is dependent on application. Solvent-based inks not recommended.
<i>Software Setting</i>	Glossy Film or Backlit Film Note: Coating technology allows more ink to pass through the backlit coating than other backlit films. As a result, high levels of ink saturation are not required to achieve optimal results.
<i>Laminating</i>	Protective laminate or backer recommended. Always use pressure sensitive laminates and a roll-fed laminator. Allow minimum 2 hour cure time before rolling.
<i>Mounting</i>	Standard mounting adhesive recommended when mounting to PVC, acrylic, etc. Never use an optically clear adhesive on coated side of this product.
<i>Storage</i>	Store in original packaging in controlled environment; 50° to 85°F, 40% to 80% relative humidity
<i>Self Life</i>	Greater than 1 year when properly stored
<i>Handling Recommends</i>	Avoid touching coated surface with bare skin. Rolls are supplied with coated surface wound out. When rolling graphics, roll so that thinner material is on outside surface of roll. Shipping/storage tubes should be at least 12" in diameter.

Ordering

IJ Polycarbonate Clear is stocked in all QMLS distribution centers and available for immediate delivery.

[Click here](#) to order online, or call 1-800-552-9427.



Quality Mounting & Laminating Systems, Inc.
285 State Street, Suite One
North Haven, CT 06473
1-800-552-9427 FAX 203 281-6451
info@qmls.com www.qmls.com

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability.