

Instabond Blockout

Instabond Blockout is a double coated ultra-thin, totally opaque mounting adhesive.



Uses:

Recycle mounting substrate with Instabond Blockout mounting adhesive. This unique pressure sensitive adhesive is completely opaque. Laminate it over a mounted print and apply a new print to the opaque adhesive surface.

Instabond Blockout can be used as a double sided adhesive for two sided retail signage that is hung in windows. Its opaque carrier prevents light from coming through the prints.

Advantages:

Opaque carrier film prevents light bleed through. Also designed to allow the multiple reuse of mounting boards in one step by recoating existing prints.

Specifications:

Adhesive	1.2 mil moderate-tack, high shear, high peel rubber
Carrier	2.3 mil metalized polypropylene
Liner	74 lb poly-coated, moisture stable, two-sided coated.
Thickness	Liner Adhesive = 1.2 mil Exposed Adhesive = 1.2 mil Carrier = 1.8 mil
Processing Range	50° to 120°F
Service Temperature Range	-40° to 180°F
Outdoor Durability	Indoor use only.
Shelf Life	1 year at 73°F, 50% relative humidity.

Catalog #	Size
0472050	51"x200'

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality will not be held responsible for customers end use of product. Quality is available for directions and advice as to proper use and application of our products.

800/552-9427

www.qmls.com