

Instant Dry White Film



Instant Dry White Film is a fast drying 5 mil white polyester film with a brilliant white gloss finish and outstanding color pop.

Uses:

Main uses include tradeshow, retail and other point of purchase displays where the highest print quality is required.

Advantages:

The instant dry feature of this product allows for faster turnaround times. It is water resistant and has a high tear resistance. The smooth surface makes it perfect for facemount prints.

Catalog #	Size
1324	24"x100'
1336	36"x100'
1342	42"x100'
1350	50"x100'
1360	60"x100'

PRINTER COMPATABILITY

Printer	Dye	Pigment
Canon Prograf Series	n/a	Best
Canon IPF Series	n/a	Best
Epson 4/7/9000 Ultrachrome	n/a	Best
Epson 4/7/9800 K3 Series	n/a	Best
HP 5000/5500 Designjet	Good*	Best
HP Z - Series	n/a	Best

*For best gas-fastness protect image w/ laminate or under glass.

PRINTER SETTINGS*

Printer	Setting
HP 5000/5500 Dye Inks	HP Basic Coated Paper
HP 5000/5500 UV Inks	HP Productivity Photo Gloss Paper
HP Z6100/3100	HP Premium Instant Dry Gloss Photo Paper
Epson Ultrachrome Inks	Epson Glossy Paper - Photo Weight Paper
Epson K3 Inks	Epson Premium Glossy Paper

*These generic printer settings are meant to be a starting point and offer good results. For best results use ICC profiles, which determine ink load and calibrate color to create an optimized print.

Specifications:

Basis Weight	180 g/m ²
Caliber	5 mil
Ink Compatibility	Epson, Canon, HP
Water Resistant	Yes
Outdoor Durability	Indoor use only.
Finishing	

Laminate with pressure sensitive laminates like Instashield UV Lustre. Facemount with Viewbond adhesive.

Protect prints imaged with dye inks under glass or laminate to increase gas-fastness.

Allow 24 hours for ink to cure before protecting image.

Laminate to extend the life of the print and increase durability.

Printing Tips: Always use gloves when handling rolls. Always print on the outside of roll. To insure best print performance of this media, clean and calibrate cartridges before loading the paper. While loading the HP 5000/5500/6100 printer, only feed 6" of paper beyond print heads. This will prevent alignment errors and banding. For best results, print in 60° to 85° and 40% to 60% RH.

Storage: New rolls - 50° to 86°F. 20 to 70% RH. Open Rolls - cover rolls with plastic bag, use end cap if storing on end. Do not stack rolls. Allow material time to adapt to room conditions.

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality will not be held responsible for customers end use of product. Quality is available for directions and advice as to proper use and application of our products.

800/552-9427

www.qmls.com