



Hard Guard Clear Texture

Hard Guard Clear Texture features a low-melt adhesive system with UV inhibitors and a textured hard-coat surface.

Uses

Hard Guard Clear Texture delivers increased bond strength and consistent quality for tradeshow displays. Its unique textured surface won't scratch or fingerprint. Unlike its competitors, Hard Guard Clear Texture is a one-piece construction that's free from silvering problems. Back with Hard Guard Light Stopper for a virtually indestructible finished product.

The QMLS difference

Because we specialize in large-format, we can offer you one of the most comprehensive, top-quality product lists available. Even more important, we've amassed an unsurpassed knowledge-base about the products and how they work together. No matter what the application, you can rest assured that the paper, ink, adhesive, and laminating film you're using are the best possible match — not just for each other, but for the end product.

Size	Catalog #
5 mil 12" x 250'	0770500
38" x 250'	0770535
51" x 250'	0770550
10 mil 12" x 250'	0770400
38" x 250'	0770435
51" x 250'	0770450

5 mil Specifications

Gauge	5.00 mil
Film	3.00 mil polyester
Adhesive	2.00 mil coextrusion
Yield	4,385 in/lb
Gloss	20, Gardner, 60°
PET Side Coefficient of Friction	0.40
Heat Seal Initiation Temp	170°F @ 40psi, 0.5 sec dwell
Useable Temp Range	190° to 245°F
UVA Absorption (315-360 nm)	85% minimum Test method Perkin-Elmer Spectrophotometer
UVB Absorption (260-315 nm)	100% Test method Perkin-Elmer Spectrophotometer

10 mil Specifications

Gauge	10.00 mil
Film	6.80 mil polyester
Adhesive	3.00 mil coextrusion
Yield	2,188 in/lb
Gloss	20, Gardner, 60°
PET Side Coefficient of Friction	0.40
Heat Seal Initiation Temp	170°F @ 40psi, 0.5 sec dwell
Useable Temp Range	190° to 245°F
UVA Absorption (315-360 nm)	85% minimum Test method Perkin-Elmer Spectrophotometer
UVB Absorption (260-315 nm)	100% Test method Perkin-Elmer Spectrophotometer

Ordering

Hard Guard Clear Texture is stocked in all QMLS distribution centers and available for immediate delivery. [Click here](#) to order online, or call 1-800-552-9427.



Quality Mounting & Laminating Systems, Inc.
285 State Street, Suite One
North Haven, CT 06473
1-800-552-9427 FAX 203 281-6451
info@qmls.com www.qmls.com