



Hard Guard Matte

Hard Guard Matte features a low-melt adhesive system with UV inhibitors and a unique hard-coat surface that won't scratch or fingerprint.

Uses

For tradeshow displays of high-quality finish and rugged durability, Hard Guard Matte is the answer. It features a low-gloss, scratch-resistant surface — plus high clarity and excellent bond to heavy ink coverage.

The QMLS difference

In today's fast-changing marketplace, we know how important it is to have a reliable source. Not just of products, but of knowledge and information. When you choose QMLS, you get someone who's as committed to the quality of your end product as you are. Someone who knows the options inside and out, and can help you choose the one that's best suited to your needs.

Size	Catalog #
5 mil	
25" x 250'	0770820
38" x 250'	0770835
43" x 250'	0770840
51" x 250'	0770850
10 mil	
12" x 250'	0770710
25" x 250'	0770720
38" x 250'	0770735
43" x 250'	0770740
51" x 250'	0770750

5 mil Specifications

Gauge	5.00 mil
Film	2.70 mil polyester
Adhesive	2 mil coextrusion
Yield	4,832 in/lb
Gloss	40, Gardner, 60°
PET Side Coefficient of Friction	0.40
Heat Seal Initiation Temp	180°F @ 40psi, 0.5 sec dwell
Useable Temp Range	180° to 245°F
UVA Absorption (315-360 nm)	85% minimum Test method Perkin-Elmer Spectrophotometer
UVB Absorption (260-315 nm)	100% Test method Perkin-Elmer Spectrophotometer

10 mil Specifications

Gauge	9.5 mil
Film	6.5 mil polyester
Adhesive	3 mil coextrusion
Yield	2,290 in/lb
Gloss	35, Gardner, 60°
PET Side Coefficient of Friction	0.40
Heat Seal Initiation Temp	180°F @ 40psi, 0.5 sec dwell
Useable Temp Range	180° to 245°F
UVA Absorption (315-360 nm)	85% minimum Test method Perkin-Elmer Spectrophotometer
UVB Absorption (260-315 nm)	100% Test method Perkin-Elmer Spectrophotometer

Ordering

Hard Guard Matte is stocked in all QMLS distribution centers and available for immediate delivery. [Click here](#) to order online, or call 1-800-552-9427.



Quality Mounting & Laminating Systems, Inc.
285 State Street, Suite One
North Haven, CT 06473
1-800-552-9427 FAX 203 281-6451
info@qmls.com www.qmls.com