



Duraguard Ultra Matte

Duraguard Ultra Matte is a heat-set laminating film that adds a non-glare matte finish without sacrificing color definition.

Uses

Perhaps the highest-quality matte laminating film on the market, Duraguard Ultra Matte is the perfect solution for situations where a non-glare finish is required or specific lighting conditions cannot be controlled. It is ideal for tradeshow displays and POPs that will be viewed under direct lighting from any different angles.

The QMLS difference

In today's fast-changing marketplace, we know how important it is to have a reliable source. Not just of products, but of knowledge and information. When you choose QMLS, you get someone who's as committed to the quality of your end product as you are. Someone who knows the options inside and out, and can help you choose the one that's best suited to your needs.

Size	Catalog #
51" x 328'	0440550
55" x 328'	0440560

Specifications	
<i>Finish</i>	Matte
<i>Base Film/ Filmic Carrier</i>	3.0 mil (75 micron) PVC (vinyl)
<i>Adhesive Bond</i>	1.0 mil (25 micron) solvent acrylic
<i>Release Liner</i>	Moisture stable paper
<i>Initial Tack</i>	Low
<i>Application Temperature</i>	180° to 210°F (82° to 99°C)
<i>Application Speed</i>	1' to 6' (0.3m to 1.75m) per minute
<i>Notes</i>	To keep film from stretching as it becomes soft and pliable when heated, apply only minimal brake tension to unwind supply shaft and release liner take-up. Adjust take-up shaft in such a way that release liner is removed just prior to entering nip rollers. By reducing adhesive's exposure to air, there is less chance of picking up dust particles.

Ordering

Duraguard Ultra Matte is stocked in all QMLS distribution centers and available for immediate delivery. [Click here](#) to order online, or call 1-800-552-9427.



Quality Media & Laminating Solutions, Inc.
285 State Street, Suite One
North Haven, CT 06473
1-800-552-9427 FAX 203 281-6451
info@qmls.com www.qmls.com

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality will not be held responsible for customers end use of product. Quality is available for directions and advice as to proper use and application of our products.