



Instabond VT

Instabond VT is a 2.0 mil polypropylene clear film that is double-coated to provide a permanent acrylic adhesive on one side and a removable acrylic adhesive on the other. It functions as a nonslip adhesive, yet removes easily and cleanly from most smooth, clean surfaces.

Uses

Instabond VT has been specially designed for short-term window graphics. It allows unimpeded outdoor viewing of indoor-mounted graphics under a variety of conditions and lights, and lifts cleanly away, leaving no adhesive residue.

The QMLS difference

In today's fast-changing marketplace, we know how important it is to have a reliable source. Not just of products, but of knowledge and information. When you choose QMLS, you get someone who's as committed to the quality of your end product as you are. Someone who knows the options inside and out, and can help you choose the one that's best suited to your needs.

Size	Catalog #
25" x 200'	0470715
38" x 200'	0470738
51" x 200'	0470740

Graphics Instructions	
<i>Compatibility</i>	Designed to be applied to smooth, indoor surfaces in good condition, including waxed commercial PVC and ceramic tile
<i>Substrate Condition</i>	Surface must be clean and dry. Any wax, paints, or coatings on surface must have good adhesion to substrate. Wait 7 days before applying decal to newly painted surface.
<i>Application Instructions</i>	Peel about 1" of release liner from top of graphic. Fold back and crease liner. Position graphic starting with top. Apply firmly using plastic squeegee. After entire graphic is applied, squeegee entire decal, working from center out, to remove air bubbles and ensure good adhesion. Make sure edges are applied well. Do not apply using the wet method.
<i>Maintenance</i>	Wait 24 hours after application before cleaning or waxing substrate. To ensure condition of graphic, avoid exposing to heavy equipment traffic.
<i>Removal</i>	Lift one edge of graphic and pull, using short quick strokes.

Specifications	
<i>Adhesive</i>	Permanent Acrylic/Removable Acrylic
<i>Carrier</i>	2 mil Polypropylene
<i>Liner</i>	Permanent adhesive is exposed when unwound on a 61 lb liner
<i>Thickness</i>	.8 mil adhesive .8 mil adhesive 2 mil carrier 3.5 mil liner
<i>Application Temperature</i>	50°F
<i>Service Temp Range</i>	-40°F to + 180°F
<i>Peel Adhesion</i>	(PSTC-1, 180° peel @ 12"/min, 73°F, on stainless steel) Permanent = 20 oz @ 15 min, 36 oz @ 24 hrs Removable = 17 oz @ 15 min, 31 oz @ 24 hrs
<i>Chemical Resistance</i>	Once applied to substrate, this product is generally found to be resistant to water, mild acids, salt, alkalis, petroleum based greases, oils, and aliphatic solvents.
<i>Outdoor Durability</i>	For indoor use only
<i>Self Life</i>	2 years at 73°F, 50% relative humidity

Ordering

Instabond VT is a QMLS exclusive. It's stocked in all QMLS distribution centers and available for immediate delivery. [Click here](#) to order online, or call 1-800-552-9427.



Quality Mounting & Laminating Systems, Inc.
285 State Street, Suite One
North Haven, CT 06473
1-800-552-9427 FAX 203 281-6451
info@qmls.com www.qmls.com

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality will not be held responsible for customers end use of product. Quality is available for directions and advice as to proper use and application of our products.