



Instashield Gloss E

Instashield Gloss E is a semi-gloss vinyl film that is a lower-cost alternative to Instashield Gloss.

Uses

For tradeshow materials, POPs, and as a laminate for vinyl banners of short duration, Instashield Gloss E delivers high quality at an economical cost. It features a thicker face film and release liner than competing products.

The QMLS difference

When you choose QMLS, you get the convenience of three fully-stocked distribution centers in Connecticut, Ohio, and Florida — allowing for same-day shipping and next-day delivery on most orders. Plus a follow-up call for every order, telling you when your products shipped, by what method, and when you can expect delivery. If your products are ever backordered, we give you the option of choosing an alternative at no additional cost to you.

Size	Catalog #
25" x 150'	0481625
31" x 150'	0481630
38" x 150'	0481637
41" x 150'	0481640
43" x 150'	0481645
51" x 150"	0481650
51" x 400'	0481660
61" x 150'	0481679

Specifications	
<i>Film</i>	Vinyl
<i>Adhesive</i>	Permanent acrylic emulsion
<i>Liner</i>	Paper
<i>Thickness</i>	Film = 3.5 mil Adhesive = 1.2 mil Liner = 90 lb
<i>Processing Range</i>	50° to 120°F
<i>Service Temp Range</i>	-40° to 180°F
<i>UV Protection</i>	UVB Block = 100% UVA Block = 80%
<i>Chemical Resistance</i>	Once applied to substrate, this product is generally found to be resistant to water, mild acid, salt, alkalis, petroleum based greases, oils, and aliphatic solvents
<i>Outdoor Durability</i>	2 years when protected from direct exposure to moisture
<i>Shelf Life</i>	2 years at 73°F, 50% relative humidity

Ordering

Instashield Gloss E is a QMLS exclusive. It's stocked in all QMLS distribution centers and available for immediate delivery. [Click here](#) to order online, or call 1-800-552-9427.



Quality Mounting & Laminating Systems, Inc.
285 State Street, Suite One
North Haven, CT 06473
1-800-552-9427 FAX 203 281-6451
info@qmls.com www.qmls.com

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability.