



## Instashield Gloss

Instashield Gloss is 1.5 or 3 mil polyester film coated with super-clear acrylic solvent adhesive.

### Uses

When extra-glossy pop is required for display applications, Instashield Gloss delivers. It's the clearest of all laminating films, resulting in enhanced color and reflectivity. Its acrylic solvent adhesive makes it a good choice for outdoor applications.

### The QMLS difference

Because we specialize in large-format, we can offer you one of the most comprehensive, top-quality product lists available. Even more important, we've amassed an unsurpassed knowledge-base about the products and how they work together. No matter what the application, you can rest assured that the paper, ink, adhesive, and laminating film you're using are the best possible match — not just for each other, but for the end product.

Size	Catalog #
1.5 mil 13" x 150'	0480610
25" x 150'	0480625
31" x 150'	0480630
41" x 150'	0480640
51" x 150'	0480650
51" x 400'	0480660
3 mil 13" x 150'	0480615
25" x 150'	0480636
31" x 150'	0480645
38" x 150'	0480637
41" x 150'	0480605
51" x 150'	0480655
51" x 400'	0480665
60" x 150'	0480675
61" x 150'	0480679

Specifications	
<i>Film</i>	Polyester
<i>Adhesive</i>	Super-clear acrylic solvent
<i>Liner</i>	Polyester
<i>Thickness</i>	<b>1.5 mil</b> Film = 1.5 mil Adhesive = 1.2 mil Liner = 1.5 mil <b>3 mil</b> Film = 3.0 mil Adhesive = 1.2 mil Liner 13"-60" widths = 1.5 mil Liner 61"-62" widths = 1.0 mil
<i>Processing Range</i>	50° to 120°F
<i>Service Temp Range</i>	-40° to 180°F
<i>UV Protection</i>	UVB Block = 100% UVA Block = 75%
<i>Chemical Resistance</i>	Once applied to substrate, this product is generally found to be resistant to water, mild acid, salt, alkalis, petroleum based greases, oils, and aliphatic solvents.
<i>Outdoor Durability</i>	2 years
<i>Shelf Life</i>	2 years at 73°F, 50% relative humidity

### Ordering

Instashield Gloss is a QMLS exclusive. It's stocked in all QMLS distribution centers and available for immediate delivery. [Click here](#) to order online, or call 1-800-552-9427.



Quality Mounting & Laminating Systems, Inc.  
285 State Street, Suite One  
North Haven, CT 06473  
1-800-552-9427 FAX 203 281-6451  
info@qmls.com www.qmls.com

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability.