



Instashield UV Lustre E

Instashield UV Lustre E is an economical, neutral finish vinyl film.

Uses

Instashield Lustre E uses the same face film and release liner as our premium Instashield Lustre — combined with an acrylic emulsion adhesive for lower cost. Its lustre finish reduces reflection without reducing color contrast, making it a good choice for tradeshow graphics and POP displays.

The QMLS difference

In today's fast-changing marketplace, we know how important it is to have a reliable source. Not just of products, but of knowledge and information. When you choose QMLS, you get someone who's as committed to the quality of your end product as you are. Someone who knows the options inside and out, and can help you choose the one that's best suited to your needs.

Size	Catalog #
25" x 150'	0481225
31" x 150'	0481230
38" x 150'	0481237
41" x 150"	0481240
41" x 400'	0481245
43" x 150'	0481247
51" x 150'	0481250
51" x 400'	0481260
61" x 150'	0481279

Specifications	
<i>Film</i>	Neutral-finish vinyl
<i>Adhesive</i>	Permanent acrylic emulsion
<i>Liner</i>	Paper
<i>Thickness</i>	Film = 3.5 mil Adhesive = 1.2 mil Liner = 90 lb
<i>Processing Range</i>	50° to 120°F
<i>UV Protection</i>	UVB Block = 100% UVA Block = 80%
<i>Chemical Resistance</i>	Once applied to substrate, this product is generally found to be resistant to water, mild acid, salt, alkalis, petroleum based greases, oils, and aliphatic solvents.
<i>Outdoor Durability</i>	2 years when protected from direct exposure to moisture
<i>Shelf Life</i>	2 years at 73°F, 50% relative humidity

Ordering

Instashield Lustre E is a QMLS exclusive. It's stocked in all QMLS distribution centers and available for immediate delivery. [Click here](#) to order online, or call 1-800-552-9427.



Quality Media & Laminating Solutions, Inc.
285 State Street, Suite One
North Haven, CT 06473
1-800-552-9427 FAX 203 281-6451
info@qmls.com www.qmls.com

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality will not be held responsible for customers end use of product. Quality is available for directions and advice as to proper use and applicaiton of our products.