



## Instashield FG

Instashield FG is a 5 mil, low-glare, rigid vinyl film formulated for floor graphics.

### Uses

Combined with Duravynyl Matte or Self Adhesive Matte — Instashield FG creates durable, high-quality floor graphics with a textured finish for protection and slip resistance. It offers an economical alternative to Instashield Polycarbonate and, unlike some competing products, features an easy-to-use pressure sensitive adhesive. It can also be combined with Instabond R when creating floor graphics from photos.

Size	Catalog #
25" x 150'	0500225
38" x 150'	0500238
43" x 150'	0500240
51" x 150'	0500250

Floor Graphics Instructions	
<i>Compatibility</i>	Designed to be applied to smooth, indoor floor surfaces in good condition, including waxed commercial PVC and ceramic tile. This product should not be laminated to any product that contains migrating plasticizers.
<i>Substrate Condition</i>	Floor surface must be clean and dry. Any wax, paints, or coatings on surface must have good adhesion to flooring substrate. Wait 7 days before applying decal to newly painted surface.
<i>Application Instructions</i>	Peel about 1" of release liner from top of graphic. Fold back and crease liner. Position graphic starting with top. Apply firmly using plastic squeegee. After entire graphic is applied, squeegee entire decal, working from center out, to remove air bubbles and ensure good adhesion. Make sure edges are applied well. <b>Do not apply using the wet method.</b>
<i>Maintenance</i>	Wait 24 hours after application before cleaning or waxing floor. To ensure condition of graphic, avoid exposing to heavy equipment traffic.
<i>Cleaning</i>	Clean scuff marks by rubbing with tennis ball. If that does not work, use isopropyl alcohol (nothing stronger).
<i>Removal</i>	Lift one edge of graphic and pull, using short quick strokes.

Specifications	
<i>Film</i>	Matte clear scuff resistant semi-rigid vinyl
<i>Adhesive</i>	Permanent acrylic
<i>Liner</i>	Polyester
<i>Thickness</i>	Film = 5 mil Adhesive = 1.2 mil Liner = 1.5 mil
<i>Processing Range</i>	50° to 90°F
<i>Minimum Application Temp</i>	50°F
<i>Servicable Temp Range</i>	-40° to +180°F
<i>Flammability</i>	Self Extinguishing
<i>Chemical Resistance</i>	Once applied to substrate, this product is generally found to be resistant to water, mild acid, salt, alkalis, petroleum based greases, oils, and aliphatic solvents.
<i>Outdoor Durability</i>	2 years
<i>Shelf Life</i>	2 years at 73°F, 50% relative humidity

### Ordering

Instashield FG is a QMLS exclusive. It's stocked in all QMLS distribution centers and available for immediate delivery. [Click here](#) to order online, or call 1-800-552-9427.



Quality Media & Laminating Solutions, Inc.  
285 State Street, Suite One  
North Haven, CT 06473  
1-800-552-9427 FAX 203 281-6451  
info@qmls.com www.qmls.com

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality will not be held responsible for customers end use of product. Quality is available for directions and advice as to proper use and application of our products.