



Mounting & Laminating → Thermal Backer Films

Hard Guard Light Stopper

Hard Guard Light Stopper is a 100% opaque white, low-melt, thermal laminating film. It features a special light-blocking foil between its adhesive layers.

Uses

Hard Guard Light Stopper was designed for use as a backing film for top-quality posters, tradeshow graphics, and POPs where high opacity and rigidity are required. It's also suited for rollable graphics and match mural displays. It can be combined with Hard Guard Clear Texture to ensure the end product stands up to the rigors of tradeshow applications.

The QMLS difference

In today's fast-changing marketplace, we know how important it is to have a reliable source. Not just of products, but of knowledge and information. When you choose QMLS, you get someone who's as committed to the quality of your end product as you are. Someone who knows the options inside and out, and can help you choose the one that's best suited to your needs.

Size		Catalog #
10 mil	25" x 250'	0880320
	38" x 250'	0880335
	51" x 250'	0880350
15 mil	25" x 200'	0880720
	38" x 200'	0880735
	51" x 200'	0880750

10 mil Specifications

<i>Gauge</i>	9.50 mil
<i>Film</i>	4.00 mil polyester
<i>Adhesive Layers</i>	0.75 mil white extrusion coating 0.30 mil foil 4.40 mil white coextrusion
<i>Yield</i>	2,360 in/lb
<i>Opacity</i>	0% transmission
<i>PET Side Coefficient of Friction</i>	0.40
<i>Heat Seal Initiation Temp</i>	170°F @ 40psi, 0.5 sec dwell
<i>Useable Temp Range</i>	190° to 245°F

15 mil Specifications

<i>Gauge</i>	15.00 mil
<i>Film</i>	7.00 mil polyester
<i>Adhesive Layers</i>	0.75 mil white extrusion coating 0.30 mil foil 7.00 mil white coextrusion
<i>Yield</i>	1,520 in/lb
<i>Opacity</i>	0% transmission
<i>PET Side Coefficient of Friction</i>	0.40
<i>Heat Seal Initiation Temp</i>	170°F @ 40psi, 0.5 sec dwell
<i>Useable Temp Range</i>	190° to 245°F

Ordering

Hard Guard Light Stopper is stocked in all QMLS distribution centers and available for immediate delivery. [Click here](#) to order online, or call 1-800-552-9427.



Quality Mounting & Laminating Systems, Inc.
285 State Street, Suite One
North Haven, CT 06473
1-800-552-9427 FAX 203 281-6451
info@qmls.com www.qmls.com

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability.