



Hard Guard White

Hard Guard White is a white laminating film with a low-melt adhesive system.

Uses

For posters, tradeshow graphics, and POPs where high opacity and flexibility are required, Hard Guard White delivers. It offers increased bond strength, consistent quality and, when combined with hard-coat thermal laminates, provides a durable end result that won't tunnel or delaminate.

The QMLS difference

When you choose QMLS, you get the convenience of three fully-stocked distribution centers in Connecticut, Ohio, and Florida — allowing for same-day shipping and next-day delivery on most orders. Plus a follow-up call for every order, telling you when your products shipped, by what method, and when you can expect delivery. If your products are ever backordered, we give you the option of choosing an alternative at no additional cost to you.

Size	Catalog #
5 mil	
25" x 250'	0670610
31" x 250'	0670620
38" x 250'	0670625
43" x 250'	0670630
51" x 250'	0670640
10 mil	
25" x 250'	0670810
31" x 250'	0670820
38" x 250'	0670825
43" x 250'	0670840
51" x 250'	0670850

5 mil Specifications	
Gauge	5.00 mil
Film	0.92 mil polyester
Adhesive	4.08 mil white coextrusion
Yield	5,160 in/lb
Opacity	11% transmission
Heat Seal Initiation Temp	170°F @ 40psi, 0.5 sec dwell
Useable Temp Range	190° to 245°F

10 mil Specifications	
Gauge	10.00 mil
Film	6.5 mil polyester
Adhesive	3.00 mil white coextrusion
Yield	2,240 in/lb
Opacity	19% transmission
PET Side Coefficient of Friction	0.40
Heat Seal Initiation Temp	170°F @ 40psi, 0.5 sec dwell
Useable Temp Range	190° to 245°F

Ordering

Hard Guard White is stocked in all QMLS distribution centers and available for immediate delivery. [Click here](#) to order online, or call 1-800-552-9427.



Quality Mounting & Laminating Systems, Inc.
285 State Street, Suite One
North Haven, CT 06473
1-800-552-9427 FAX 203 281-6451
info@qmls.com www.qmls.com

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability.