



# Mounting & Laminating → Thermal Laminating Films

## Digi Guard Satin

Digi Guard Satin is a crisp, clear semi-gloss film with a low-melt adhesive system and UV inhibitors.

### Uses

For ink jet, plain paper, and photographic prints, Digi Guard Satin provides enhanced clarity and ink preservation. It's suitable for single- or double-sided application, providing added rigidity and protection from abrasions, moisture, oils, and dirt. It exhibits excellent adhesion and consistent roll uniformity. Digi Guard Satin is available in widths up to 76". When images are ink jet printed, our Quality Satin Paper and Ink Jet Coated Media have been specially designed to work with Digi Guard Satin for superior end results.

### The QMLS difference

Quality comes first at QMLS. We find the best solutions for your mounting and laminating needs and bring them to you... on time and on budget. So you never have to worry about waste, reprinting, or relaminating.

Size		Catalog #
3 mil	25" x 500'	0890515
	31" x 500'	0890520
	38" x 500'	0890525
	43" x 500'	0890530
	51" x 500'	0890540
	55" x 500'	0890560
	60" x 500'	0890570
5 mil	25" x 500'	0891515
	31" x 500'	0891520
	38" x 500'	0891525
	43" x 500'	0891530
	51" x 500'	0891540
	55" x 500'	0891560
	62" x 500'	0891580
	76" x 500'	0891590

### 3 mil Specifications

Gauge	3.00 mil
Film	0.48 mil polyester
Adhesive	2.52 mil
Yield	9,230 in/lb
PET Side Coefficient of Friction	0.45 to 0.55
Heat Seal Initiation Temp	170°F @ 40psi, 0.5 sec dwell
Useable Temp Range	185° to 195°F
UVA Absorption (315-360 nm)	85% minimum Test method Perkin-Elmer Spectrophotometer
UVB Absorption (260-315 nm)	100% Test method Perkin-Elmer Spectrophotometer

### 5 mil Specifications

Gauge	5.00 mil
Film	2.00 mil polyester
Adhesive	3.00 mil
Yield	5,000 in/lb
PET Side Coefficient of Friction	0.45 to 0.55
Heat Seal Initiation Temp	170°F @ 40psi, 0.5 sec dwell
Useable Temp Range	185° to 195°F
UVA Absorption (315-360 nm)	85% minimum Test method Perkin-Elmer Spectrophotometer
UVB Absorption (260-315 nm)	100% Test method Perkin-Elmer Spectrophotometer

### Ordering

Digi Guard Satin (except 62" and 76" widths) is stocked in all QMLS distribution centers and available for immediate delivery. 62" and 76" widths are a custom order and ship in approximately 5 business days. [Click here](#) to order online, or call 1-800-552-9427.



Quality Mounting & Laminating Systems, Inc.  
285 State Street, Suite One  
North Haven, CT 06473  
1-800-552-9427 FAX 203 281-6451  
info@qmls.com www.qmls.com

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability.