

PDQ Photo Satin/PDQ Photo Gloss Papers



PDQ Photo Satin Paper and PDQ Photo Gloss Paper are 8 mil, bright white photo papers designed for today's wide gamut pigment ink photo quality printers such as Canon, Epson and HP. The microporous topcoat means your prints will be instantly dry and water resistant. Both papers have superior shadow detail and extremely low dot gain.

Uses:

Wide format full-color printing of any photographic or display graphic. Recommended for any printer using UV, pigment inks. When using dye inks, it is recommended that print be laminated within 24 hours to prevent the image from fading. Can be hot or cold laminated.

Advantages:

Specially formulated to work with the new generation of UV pigment printers for excellent print quality and super fast dry times. Perfect for high resolution images up to 1440dpi. Very economical price.

Catalog #	Size	Catalog #	Size
Gloss		Satin	
3624	24"x100'	2824	24"x100'
3636	36"x100'	2836	36"x100'
3642	42"x100'	2842	42"x100'
3650	50"x100'	2850	50"x100'
3660	60"x100'	2860	60"x100'

Printer Settings

HP Z-6100	HP Gloss Instant Dry Photo Paper
HP 5000/5500 dye or UV	Productivity Mode - Photo Gloss Paper Setting
Epson 4000/7000/9000 Ultrachrome Ink	Premium Glossy
Epson 4000/7000/9000 K3 Series	Premium Semi-Gloss
Canon IPF	HW Semi-Gloss Photo

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality will not be held responsible for customers end use of product. Quality is available for directions and advice as to proper use and application of our products.

Specifications PDQ Gloss

Thickness	8 mil
Weight	200g/m ²
Gloss Level (60°)	Gloss 45 Satin 21
Opacity	97%
Waterfast/ Waterproof	Water Resistant
Finishing	Allow print to dry 12-24 hours before lamination for best results. Use low melt thermal DigiGuard or pressure sensitive Instashield to extend the life of the print.
Converting	Coated side out.
Shelf Life	12 months at storage conditions noted below.

Printing Tips: Always use gloves when handling rolls. Always print on the outside of roll. To insure best print performance of this media, clean and calibrate cartridges before loading the paper. While loading the HP 5000/5500/6100 printer, only feed 6" of paper beyond print heads. This will prevent alignment errors and banding. For best results, print in 60° to 85° and 40% to 60% RH.

Storage: New rolls - 50° to 86°F. 20 to 70% RH. Open Rolls - cover rolls with plastic bag, use end cap if storing on end. Do not stack rolls. Allow material time to adapt to room conditions.

800/552-9427

www.qmls.com