

Polypropylene Satin Film



Polypropylene Satin Film is a waterfast, tear resistant, smooth white film for indoor use with dye ink or short term outdoor use with UV pigment inks.

Uses:

Main uses include banners, POP, signage, banner stands and applications where you want to eliminate the chance that the media can split like paper

Advantages:

Polypropylene Satin Film has the advantages of a polyester film (won't split) and the cost of a photo paper. It won't tear and for short term applications, it does not require lamination. It can be grommeted and is waterfast with dye inks and UV inks.

Specifications:

| | |
|------------------------|--|
| Basis Weight | 34 lb |
| Caliber | 7.5 mil |
| Ink | Dye or UV/Pigment |
| Waterfast / Waterproof | Waterfast with dye. Waterproof with UV pigment ink. |
| Outdoor Durability | 3 months unlamimated when printed with UV inks. 6 months when printed with UV inks and laminated. |
| Finishing | Will accept pressure sensitive laminates like Instashield UV Lustre or thermal laminates like any DigiGuard or HardGuard laminate. |

| Catalog # | Size |
|-----------|-----------|
| 4436 | 36" x 66' |
| 4442 | 42" x 66' |
| 4450 | 50" x 66' |
| 4460 | 60" x 66' |

PRINTER COMPATABILITY

| Printer | Dye | UV |
|--------------------------------------|-----|----|
| Pro600e/630/700/750/850/10000 | X | X |
| HP 2000,3000,5000 Series | X | X |
| HP Z3100, Z6100 | X | X |
| Mimaki JV2, JV4 | | X |
| Roland HiFi Jet | X | X |
| Epson 3000, 7000, 9000, 10000 series | X | X |

PRINTER SETTINGS

| Printer | Ink | Setting |
|--------------|---------------|----------------|
| HP 5000/5500 | Dye or UV Ink | Outdoor Vinyl |
| HP Z6100 | | Outdoor Banner |
| Epson 10000 | Dye or UV Ink | Outdoor Banner |

Printing Tips: Always use gloves when handling rolls. Always print on the outside of roll. To insure best print performance of this media, clean and calibrate cartridges before loading the paper. While loading the HP 5000/5500/6100 printer, only feed 6" of paper beyond print heads. This will prevent alignment errors and banding. For best results, print in 60° to 85° and 40% to 60% RH.

Storage: New rolls - 50° to 86°F. 20 to 70% RH. Open Rolls - cover rolls with plastic bag, use end cap if storing on end. Do not stack rolls. Allow material time to adapt to room conditions.

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality will not be held responsible for customers end use of product. Quality is available for directions and advice as to proper use and application of our products.

800/552-9427

www.qmls.com