

Instashield

Premium Cast Laminates



Instashield Premium Cast laminates are high performance 2 mil cast vinyl films formulated for extended outdoor durability and maximum conformability.

Uses:

When long term outdoor durability required. A choice of three finishes are available, each are backed with a 50 lb poly-coated release liner (Premium Cast Gloss Plus Film features a polyester release liner which yields crystal clear wet out of the adhesive, perfect for use with one way vision materials like Classic View Window Film.) These overlaminate films are recommended for use with DuraVinyl 500 Series printable adhesive vinyl. Perfect for applications that require conformability to complex curves or varied surfaces such as vehicle and fleet graphics.

Premium Cast Gloss

Catalog #	Size
0520048	48x150
0520054	54x150
0520060	60x150

Premium Cast Matte

Catalog #	Size
0520148	48x150
0520154	54x150
0520160	60x150

Premium Cast Lustre

Catalog #	Size
0520248	48x150
0520254	54x150
0520260	60x150

Premium Cast Gloss Plus

Catalog #	Size
0520348	48x150
0520354	54x150
0520360	60x150

Specifications:

<i>Film</i>	Premium clear cast vinyl.
<i>Adhesive</i>	Permanent acrylic.
<i>Liner</i>	Gloss, Matte, Lustre =Glassine Gloss Plus = Polyester
<i>Thickness</i>	Film = 2.0 mil Liner = 50lb. Gloss Plus Liner = 1.2m
<i>Processing Range</i>	50° to 100°F
<i>Service Temp Range</i>	-50° to +225°F
<i>UV Protection</i>	UVB Block = 100% UVA Block = 80%
<i>Chemical Resistance</i>	Once applied to substrate, these products are generally found to be resistant to water, mild acid, salt, alkalis, petroleum based greases, oils and aliphatic solvents.
<i>Outdoor Durability</i>	7 years
<i>Shelf Life</i>	2 years at 73°F, 50% RH

Longer rolls available on request.

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality will not be held responsible for customers end use of product. Quality is available for directions and advice as to proper use and application of our products.

800/552-9427

www.qmls.com