



Gallery Bond

Gallery Bond

Gallery Bond is a 3 mil unsupported pressure sensitive adhesive wound on a single poly-coated release liner. It is formulated for demanding applications such as bonding to low surface energy substrates.

Uses

Gallery Bond is used to adhere a board (typically DiBond) to the back of an acrylic face mount to sandwich the print between the two boards.

- Can be used wherever a high coat weight adhesive is required
- Bonding to slightly textured surfaces

Advantages

- Quick initial tack
- High peel and shear properties
- Excellent service temperature range
- Conformable with good dimensional stability

Size

60" x 150'

Catalog

0470560

Specifications

Adhesive	3 mil clear unsupported acrylic
Liner	5.5 mil polycoated kraft
Laminating Temperature	68°F to 100°F
Service Temperature Range	-30°F to 375°F
Shelf Life	1 year at 73°, 50% RH

Ordering

Gallery Bond is a Quality Media and Laminating Solutions exclusive product. It is stocked in all of our distribution centers and available for immediate delivery. To place an order, call us at 1-800-552-9427.

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products.