



InstaShield UV Gloss

InstaShield UV Gloss

InstaShield Gloss is 1.5 or 3 mil polyester film coated with super-clear acrylic solvent adhesive.

Uses

When extra-glossy pop is required for display applications, InstaShield Gloss delivers. It's the clearest of all laminating films, resulting in enhanced color and reflectivity. Its acrylic solvent adhesive make it a good choice for outdoor applications.

The Quality Media Difference

Because we specialize in large-format, we can offer you one of the most comprehensive, top-quality product lists available. Even more important, we've amassed an unsurpassed knowledge-base about the products and how they work together. No matter what the application, you can rest assured that the paper ink, adhesive, and laminating film you're using are the best possible match – not just for each other, but for the end product.

Size	Catalog #
1.5 MIL	
25" x 150'	0480625
31" x 150'	0480630
51" x 150'	0480650
51" x 400'	0480660
54" x 150'	0480654

3 MIL	
25" x 150'	0480636
38" x 150'	0480637
51" x 150'	0480655
51" x 150'	0480665
61" x 164'	0480679

Specifications

Film	Polyester
Adhesive	Super-clear acrylic solvent
Liner	Polyester
Thickness	1.5 mil Film = 1.5 mil Adhesive = 1.2 mil Liner = 1.5 mil 3 mil Film = 3.0 mil Adhesive = 1.2 mil Liner 13"-60" widths = 1.5 mil Liner 61" width = 1.0 mil
Processing Range	50°F to 120°F
Service Temperature Range	-40°F to + 180°F
UV Protection	UVB Block = 100% UVA Block = 75%
Chemical Resistance	Once applied to substrate, this product is generally found to be resistant to water, mild acid, salt, alkalis, petroleum bases greases, oils, and aliphatic solvents.
Outdoor Durability	3 years
Shelf Life	2 years at 73°F, 50% relative humidity

Ordering

InstaShield UV Gloss is a Quality Media and Laminating Solutions exclusive product. It's stocked in all of our distribution centers and available for immediate delivery. To place an order, call us at 1-800-552-9427.

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products.